

## SpEctop CPD Primer SB

CAR PARK DECK SOLVENT-BASED PRIMER

### DESCRIPTION

**SpEctop CPD Primer SB** is a two-part, solvent based low viscosity epoxy resin, for priming concrete surfaces prior to the application of the **SpEctop CPD System**.

### TYPICAL USES

**SpEctop CPD Primer SB** is suitable for providing an excellent bond between cementitious surfaces and the **SpEctop CPD System** range.

### ADVANTAGES

**SpEctop CPD Primer SB** has low viscosity properties, which enable the material to penetrate the substrate. This penetration and the chemical bond, which forms between the primer and the subsequently applied topping, provides a bond greater than the cohesive strength of the parent concrete.

### TECHNICAL DATA

#### Typical results @ 25 °C

<b>Specific gravity</b>	0.97
<b>Pull-off strength (ASTM D4541)</b>	3.0 N/mm <sup>2</sup>


### APPLICATION

#### Preparation

It is essential that adequate preparation is carried out prior to the application of **SpEctop CPD Primer SB** such as grit blasting. This preparation should ensure the removal of all grease, oil and loose material.

#### Mixing

**SpEctop CPD Primer SB** is supplied in a two-component kit consisting of a pigmented curing agent and a base component.



The contents of the curing agent tin should be emptied into the base component and stirred with a spatula until the product appears uniform.

### Application

The mixed primer should then be applied to the prepared substrate by a stiff brush. Care should be taken to avoid over application.

If the primer is easily absorbed into the floor, it will be necessary to apply a second coat once the initial coat is tack free.

### PACKAGING AND YIELD

**SpEctop CPD Primer SB** is supplied in 1, 5 and 15 litre units. The theoretical coverage rate is 10-15 m<sup>2</sup>/litre.

### EQUIPMENT CLEANING

All equipment may be cleaned of uncured material using **SpEctop Cleaning Fluid**.

### APPLICATION TEMPERATURE RANGE

Minimum	5 °C
Maximum	35 °C

At temperatures above this range the pot life of the material will be reduced, therefore the material should be stored in a cool environment.

### STORAGE AND SHELF LIFE

**SpECTop CPD Primer SB** has a shelf life of 12 months when stored in original containers in a cool, dry environment.

### HEALTH AND SAFETY

Contact with skin and eyes should be avoided. It is essential that adequate ventilation is provided and that all personnel avoid inhaling the vapours produced. If working is necessary in a confined area it is strongly recommended that sealed respiratory equipment is utilised.

<b>Eye contact</b>	Rinse with copious amounts of clean water and seek medical attention.
--------------------	---

### Skin contact

Rinse with copious amounts of clean water followed by thorough cleaning with soap and water.

DO NOT USE SOLVENTS

### Ingestion

Seek immediate medical attention.

DO NOT INDUCE VOMITING

### FLAMMABILITY

**SpECTop CPD Primer SB & SpECTop Cleaning Fluid** are flammable. Do not expose to naked flame or other sources of ignition.

### FLASHPOINT

<b>SpECTop CPD Primer SB</b>	>60 °C
<b>SpECTop Cleaning Fluid</b>	>40 °C

Issue 4: 01/2011

QA-054

Whilst the information and/or specifications given are, to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors as the conditions of use and labour involved are beyond our control.

If it is proven that the product does not perform as described in our TDS, SpEC's liability extends solely to the free replacement of product, once the claim has been accepted after due investigation by SpEC. SpEC will not entertain any claims involving any form of consequential costs or damages such as shipping costs, custom duties, damages to third parties, damages to structures, penalties from delay of a project or any other form of consequential damage.

### SPECIALITY ENGINEERING CHEMICALS

PO Box 61347, Dubai, United Arab Emirates. Telephone: +971 4 883 6662, Fax: +971 4 883 7696  
E-mail: info@spec.ae; Skype ID: spec.sales

www.spec.ae